

# WATER FLOW SWITCH

## STANDARD FLOW RATE -S.P.D.T.

### MODEL :- RC-61



"RC" make Flow Switch is designed for use on Non-Viscous liquid, Water, Methyl Glycol Solutions or any other liquid not injurious to Brass & Non-Ferrous Metal parts that come in the contact with the liquid. The SPDT contacts make or break and electrical circuit when flow starts or stops.

### Can be used in :

- Water purification and treatment systems
- Booster pumps
- Fast Shut down on high input boilers to guard against circulation failure
- Cooling systems for electronic tube, bearing & compressor
- Can be used any where, who wants to take Flow, No-Flow signal.

They can be wired to close circuit and open a second Circuit. When liquid flow either exceeds or drops below the Adjusting flow rate.

Pipe Connection                    25 mm BSMPT  
 Type                                    On-Line type.  
 Max. Liquid Pressure            150 PSIG.  
 Max. Liquid Temperature       110' C  
 Min. Liquid Temperature       1' C



ELECTRICAL RATING			
MOTOR RATING	120 V	208 V	240 V
HORSEPOWER	1	1	1
A.C. FULL LOAD Amps.	16	8.8	8
A.C. LOCKED ROTOR Amps.	96	52.8	48
NON-CONDUCTIVE LOAD Amps	16	16	16
PILOT DUTY -125VA. 24/240V A.C.			

FLOW CONTROL RANGE											
PIPE SIZE		25mm	32mm	40mm	50mm	65mm	80mm	100mm	125mm	150mm	200mm
MIN ADJUSTMENT	On-Flow	4.2	5.6	7.5	13.7	17.5	27.5	37.1	57.2	77	201.1
	Off-Flow	2.5	3.5	5	9.5	12	19	27.9	41	54	170.3
MAX. ADJUSTMENT	On-Flow	9.3	13.3	17.7	27	31	50	81	118	144	415
	Off-Flow	9	12.5	16.5	25	28.8	47	76	111	135	400

(All of the above values are in G.P.M.)  
 (The above data is experimental data, it may have a tolerance of 10%)

Address :- B-47, Block B, Mayapuri Industrial Area Phase I, Mayapuri, New Delhi, 110064  
 E-Mail ID :- info@rapidcontrols.in, sales1@rapidcontrols.in, sales3@rapidcontrols.in  
 Phone No. :- +91-9971998828, +91-9971998824, +91-9971998871, +91-8743854385

web: [rapidcontrols.in](http://rapidcontrols.in)